

Hitachi FX-Duo Interactive Whiteboard

# Robust reliability that's truly hands on

Introducing the interactive whiteboard that's so versatile you can use either an electronic pen or finger.



The new DuoBoard also offers a hard, durable screen – not a membrane – that's hard to damage and that can be used by multiple users. It works as a dry-wipe board, too. In fact, the DuoBoard combines all the best features of all previous whiteboards, without limitations.

Until now, your interactive whiteboard came with a choice: electronic pen-driven or stylus/finger-driven.

Now you don't have to choose. The Hitachi FX-DuoBoard comes with a hard, damage-resistant screen. It responds to pen or finger. Its low-reflection surface is kind on the eyes. And it caters for multiple users at once. So, it's great for educational games.

#### Key Benefits

- Constant learning – robust surface means no downtime
- Flexible learning – can use finger or electronic pen
- Interactive group work – two or more can use board at once
- Kind to your eyes – low-reflection surface coating.

Redefining the interactive whiteboard

**HITACHI**  
Inspire the Next


# FX-Duo at a glance:

- Robust surface - The surface is robust and the whiteboard works even if there are scratches/dents on the surface.
- Low reflection - Projector reflection is minimized making it gentle on the eyes.
- Input Methods - use a finger/object or an electronic Pen to operate the whiteboard
- Simultaneous Inputs -Operate the whiteboard using both hands (gestures). Scroll and Zoom-in/Zoom-out.
- Field Replaceable Digitizer – A detachable digitiser makes it unnecessary to send the whole unit for repairing.
- Electronic Pen. Includes three side buttons

## Specifications - FX-DUO-77

<b>Model No.</b>	AH00179
<b>Input Methods:</b>	Image sensor and infrared method
<b>Interface to Computer:</b>	USB 1.1, 2.0
<b>Effective Screen Size</b>	77 Inches (1,573 mm (W) x 1,180mm (H))
<b>Sampling Rate</b>	Approximately 100 points/sec
<b>Resolution</b>	Approximately 0.05 mm
<b>Accuracy</b>	Approximately ±1.5 mm
<b>Board/Surface Material</b>	Lauan wood + EPS (core), Colour steel boards (surface), Fluorine film (front surface coating)
<b>Operating Specification</b>	5 – 35 Celsius, 20 – 80% Humidity without condensation
<b>Dimensions(mm)</b>	1,743(W) x 1,357(H) x 56(D)
<b>Dimensions w/ floor stand (mm)</b>	1,743(W) x 1,824 – 2,174(H) x 620(D)
<b>Weight (main unit)</b>	24kg
<b>Weight (w/ floor stand)</b>	41kg
<b>Packing dimension (main unit) (mm)</b>	1,870(W) x 1,560(H) x 130(D)
<b>(floor stand) (mm)</b>	1,650(W) x 280(D) x 80(H)
<b>Packing weight (main unit)</b>	34kg
<b>(floor stand)</b>	18.5kg
<b>Certificates</b>	FCC, CE, UL
<b>Warranty</b>	Five-year limited equipment warranty upon registration. See hardware manual for details.

\*1 The battery life varies according to the temperature and the usage environment. The life time of full recharging is approximately 500 times.



**Hitachi Software Engineering (UK) Limited**  
Interactive Media Solutions Division  
Tel: +44 (0)207 246 6868  
Fax: +44 (0)207 246 6860  
Email: sales@hitachi-software.co.uk

**Hitachi Software Engineering France S.A.S**  
Interactive Media Solutions Division  
Tel: +33 (0)153 827 600  
Fax: +33 (0)153 827 619  
Email: starboard@hitachisoft-eu.com

**Hitachi Software Engineering Europe AG**  
Interactive Media Solutions Division  
Tel: +49 (0)30 8877 2600  
Fax: +49 (0)30 8877 2610  
Email: starboard@hitachisoft.de

[www.hitachisoft-eu.com](http://www.hitachisoft-eu.com)

Further information:



[www.infomat.es](http://www.infomat.es)  
977 33 00 84  
[ventas@infomat.es](mailto:ventas@infomat.es)

**HITACHI**  
Inspire the Next